Material	High Conductivity Seamless Copper Tube				
Plating	Electro-Tin				
Wire Size	8 AWG				.48 R Ref
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric		NA N		Color coded barrel markings
Wire Strip Length	3/4 in.	.60±.04		N23 8 STR CU LCC8-38D	PANDUIT
Stud Size	3/8 in.			- =	
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.36±.04 -	-	- 1.00±.02	2
UL Temperature Rating	90° C				
C.S.A Certified Wire Connector	Yes				
Panduit Color Code on Barrel	RED				
Panduit Die Index No. on Barrel	P21				70±.04 Beveled wire
Alternate Industry Die Index No. () on Barrel	N/A		ı		entry .18±.01 .27±.01
CERTIFIED		5±.01			
					CORP. TINLEY PARK, ILLING

10333

ECN SCALE

N/A

RELEASED

DESCRIPTION

12/02 SAB DRL

BY CHK

00

REV DATE

LCC8-38D-L Copper Lug - Two-Hole, Long Barrel

LCC8-38D-CUST

DRAWING NO / CAD FILE