



**CONFIDENTIAL & PROPRIETARY INFORMATION**

This document contains Confidential and Proprietary Information of Alliance LLC, and all design, manufacturing, reproduction, use, and sale rights of such information are expressly reserved

ALL DIMENSIONS ARE IN MM



**NOTES:**

- MAGNET PROPERTIES PER N-35:  
 Br: 11,700-12,200 G  
 Hc: 10,800-12,000 Oe  
 Hci: ≥12,000 Oe  
 Tmax: 80 C
- SUPPLIED MAGNETIZED THROUGH THE THICKNESS
- PARTS ARE NICKEL PLATED FOR 15hrs SALT SPRAY MIN.



REV	DESCRIPTION	DATE	BY
B	Changed CAD, incl cert, 3D	1/30/14	BT

TOLERANCES (UNLESS OTHERWISE NOTED)	
DECIMAL	METRIC
X.XX = ± .01	X.X = ± .25
X.XXX = ± .005	X.XX = ± .13
ANGLES ± .5°	
DO NOT SCALE DRAWING	

<b>Alliance LLC</b> 1450 CLARK DRIVE, VALPARAISO, INDIANA 46385		
DESCRIPTION: 5.0 mm x 2.5 mm DISC MAGNET		
<b>SENSOR MAGNET</b>		<b>P/N: ALC5025T</b>
GRADE: N-35	Drwg by: BT	REV LEVEL: B
COATING: Nickel	Appr by: DV	Appr. Dated: 05-15-2013